


# CLIMATEGUARD® ULTRAVIEW

ClimateGuard UltraView Vinyl Patio Door Features and Options

Patio Door

Construction Features	Fusion welded corners on main frame and sash	Standard
	Made from high-grade solid vinyl extrusions	Standard
	Height adjustable steel, zinc-coated tandem wheels	Standard
	4 3/4" jamb depth	Standard
	Stainless steel track	Standard
	Interlocking sash meeting rails	Standard
	Galvanized steel reinforcement and interlock stiles	Standard
	Snap-in glazing system	Standard
Frame Colors	Multi-chambered thermal insulated system	Standard
	White	Standard
	Beige	Optional
	Cocoa	Optional
Hardware	Painted exterior with white interior	Optional
	Keylock cylinder	Standard
	Foot lock	Standard
	Oak handleset	Standard
	Solid white or brass handleset	Optional
Custom Size Options <sup>1</sup>	Intuition lock with 2 point locking system	Optional
	Minimum width	60"
	Minimum height	80"
	Maximum width	96"
Glass Options <sup>2</sup> 1" insulated warm edge	Maximum height	85"
	Tempered glass	Standard
Builders' Options	 U-Shield Pro: Double Coated LoE <sup>2</sup> -270, Clear - Argon gas filled	Optional
	Nailing flange	Standard
Screen	Mullion kit	Optional
	Half fiberglass screen	Standard
Grids <sup>3</sup>	Colonial grid	Optional
	Prairie grid	Optional
Warranty	Lifetime Limited Warranty	Standard



<sup>1</sup> Standard sizes: 5', 6', and 8'. Custom sizes available; ask your salesperson for details

<sup>2</sup> Custom glass options available; ask your salesperson for details

<sup>3</sup> Other grid options available; ask your salesperson for details



Stock Vinyl Extrusions

Painted Exterior Frame Colors with White Interior