CLIMATEGUARD® ULTRAVIEW

FEATURES & BENEFITS

Whether building or remodeling your home, the UltraView Vinyl Window is the builder's choice. It is versatile, energy-efficient, and maintenance-free, all at a great value. UltraView is as practical as it is beautiful. Its design creates a clean, simple look and provides a maximized viewing area.

THERMAL EFFICIENCY
Effective thermal insulator
Better protection against condensation

STRUCTURAL DURABILITY
Better impact testing
Better flexibility

WEATHER RESISTANCE
Resistant to water & light
Superior color retention

DESIGN CUSTOMIZATION
Solid interior colors
& painted exterior options

- Fusion welded corners on main frame and sash
- Offered with or without integral nailing flange
- Internal cavities placement optimized for thermal performance
- Weatherstripping standard on head and sill for increased protection
- Double and triple glazing options available
- Constant force or spiral balance systems
- Color-matched locks standard on all windows
- Interlocking sash meeting rails
- Tilt in or removable sashes
- Two standard colors available with exterior painted options
- Stepped sill
- Triple Weather Seal
- Made from high grade vinyl extrusions

UltraView Double Hung Shown

MADE IN U.S.A. CLIMATEGUARD®

(773) 278-3600
WWW.CLIMATEGUARDWINDOWS.COM

CLIMATEGUARD®
ULTRAVIEW

Double Hung
Single Hung

2-Lite Slider
3-Lite Slider

Casement

Picture

Bay & Bow Window

Awning

Special Shape

Escape Window

COLOR & FINISH OPTIONS

The UltraView Vinyl Window features three maintenance-free, high performance stock frame colors. Multiple options available with painted exterior finishes and a white interior finish.

STOCK VINYL EXTRUSIONS

White

Beige

PAINTED FRAME OPTIONS *exterior*

Beige | Clay | Cocoa | Bronze | Green | Black

interior

Dark Oak with White exterior | Light Oak with White exterior

MADE IN THE U.S.A. CLIMATEGUARD®

(773) 278-3600
WWW.CLIMATEGUARDWINDOWS.COM

ENERGY STAR

CLIMATEGUARD®
WINDOWS & DOORS

USHIELD
PERFORMANCE GLASS PACKAGES

LIMITED LIFETIME WARRANTY
FOR RESIDENTIAL USE

ULTRAVIEW DOUBLE HUNG WINDOW

PERFORMANCE GLASS PACKAGES	USHIELD PRO ESSENTIAL WEATHER PROTECTION	USHIELD PLUS SUPERIOR ENERGY EFFICIENCY	USHIELD MAX MAXIMUM PROTECTION & EFFICIENCY
	GOOD	BETTER	PREMIUM
U-FACTOR	.30	.26	.23
SOLAR HEAT GAIN COEFFICIENT	.29	.28	.25
VISIBLE TRANSMITTANCE	.55	.51	.43
AIR LEAKAGE	.04	.04	.04
THERMAL PERFORMANCE	❄	❄❄	❄❄❄
COST	$	$$	$$$
CARDINAL GLASS	DOUBLE COATED LOE²-270, CLEAR	DOUBLE COATED LOE²-270, EPS	DOUBLE COATED LOE²-270, CLEAR, LOE²-270
GLASS UNIT	7/8" DOUBLE PANE	7/8" DOUBLE PANE	7/8" TRIPLE PANE
GAS FILL	ARGON	ARGON	ARGON
SPACER SYSTEM	INTERCEPT WARM EDGE	INTERCEPT WARM EDGE	INTERCEPT WARM EDGE

NEAT GLASS, TEMPERED, FROSTED, LAMINATED GLASS & OTHER OPTIONS AVAILABLE

MADE IN THE U.S.A. CLIMATEGUARD®

(773) 278-3600
WWW.CLIMATEGUARDWINDOWS.COM

CLIMATEGUARD® ULTRAVIEW

ClimateGuard UltraView Vinyl Windows Features and Options

		Window Types								
		Double Hung (2000 or 2550 Series)	2 Lite Slider (2000 Series)	3 Lite Slider (2000 Series)	Casement (4000 Series)	Awning (4000 Series)	Picture (2000 or 4000 Series)	Bay	Bow	Escape Window (2000 Series)
Construction Features	Fusion welded corners on main frame and sash	S	S	S	S	S	S	S	S	S
	Made from high-grade solid vinyl extrusions	S	S	S	S	S	S	S	S	S
	Stepped jamb construction	S	S	S	S	S	-	S	S	S
	3 1/4" jamb depth	S	S	S	S	S	S	S	S	S
	Tilt-in or removable sashes	S	S	S	S	S	-	S	S	S
	Interlocking sash meeting rails	S	S	S	S	S	-	S	S	-
	Constant force or spiral balance systems	O	-	-	-	-	-	-	-	-
	Stepped Sill	S	S	S	S	S	-	S	S	-
	Foam Filled	O	O	O	-	-	-	-	-	-
	Multi-chambered thermal insulated system	S	S	S	S	S	S	S	S	S
Frame Colors	White	S	S	S	S	S	S	S	S	S
	Beige	O	O	O	O	O	O	O	O	O
	Painted exterior with white interior	O	O	O	O	O	O	O	O	O
Hardware	Double sash locks[1]	S	S	S	-	-	-	-	-	S
	Deluxe vent latch	S	-	-	-	-	-	-	-	-
	Multiple locking system	-	-	-	S	S	-	S	S	-
	Folding handle	-	-	-	S	S	-	S	S	-
	Egress Hinge	-	-	-	O	-	-	-	-	
Custom Size Options[2]	Minimum width	16"	33"	64"	14"	16"	14"	60"	72"	16"
	Minimum height	35"	19"	19"	20"	14"	14"	48"	48"	16"
	Maximum width	45"	84"	100"	34"	60"	70"	120"	120"	36"
	Maximum height	74"	60"	60"	70"	36"	70"	72"	72"	36"
Glass Options 7/8" insulated warm edge	Clear glass	S	S	S	S	S	S	S	S	S
	U-Shield Pro: Double Coated LoE²-270, Clear	O	O	O	O	O	O	O	O	O
	U-Shield Plus: Double Coated LoE²-270, EPS LoE	O	O	O	O	O	O	O	O	O
	U-Shield Max: Double Coated LoE²-270, Clear, LoE²-270	O	O	O	O	O	O	O	O	O
	Tempered, Frosted, Tinted, Laminated	O	O	O	O	O	O	O	O	O
Builders' Options	Nailing flange	O	O	O	O	O	O	O	O	O
	Mullion kit	O	O	O	O	O	O	O	O	O
Screen	Half fiberglass screen	S	S	S	-	-	-	O	O	-
	Full fiberglass screen	O	O	O	S	S	-	O	O	O
	Half aluminium screen	O	O	O	-	-	-	O	O	-
	Full aluminium screen	O	O	O	O	O	-	O	O	O
Grids[3]	Colonial grid	O	O	O	O	O	O	O	O	O
	Prairie grid	O	O	O	O	O	O	O	O	O
Warranty	Lifetime Limited Warranty	S	S	S	S	S	S	S	S	S

ENERGY STAR

[1] Standard on double hung 30" wide or wider; optional under 30" wide
[2] Sizes may vary; ask your salesperson for details
[3] Other options available; ask your salesperson for details

(S) Standard (O) Optional (-) Not Available